## Dwyer. **SERIES TE-E/N** WALL MOUNT TEMPERATURE SENSORS 1 - 1/161-5/32 1 - 3/16[27.05] [29.39] [30.00] **Discrete Wall Mount Housing** 3X-5/32 [3.87] 21/64 3-21/32 [8.38] [92.96] G алалалал 3X-3/8 [9.36] 3-9/16 European [90.42] 35/64 27.69 [14.02] 2X-11/64 [4.47] 3-1/64 4-1/2 œ 12244447 [114.30] [76.56] 2-51/64 31/64 [12.32] [71.12] European North American North American

The Series TE-E/N Wall Mount Temperature Sensors provide a low cost temperature input for any building management system.

## FEATURES/BENEFITS

- · North American or European housing aesthetic options
- · Uniform look matches other Dwyer wall mount devices
- · Universal mounting plate meets various installation requirements

## APPLICATIONS

- Building automation
- Room temperature monitoring

MODEL CHART			
North American Model	Sensor Type	European Model	Sensor Type
TE-NND-A	10k Ω type III thermistor	TE-END-A	10k Ω type III thermistor
TE-NND-B	10k Ω type II thermistor	TE-END-B	10k Ω type II thermistor
TE-NND-C	3k Ω thermistor	TE-END-C	3k Ω thermistor
TE-NND-D	Pt100 Ω RTD	TE-END-D	Pt100 Ω RTD
TE-NND-E	Pt1000 Ω RTD	TE-END-E	Pt1000 Ω RTD
TE-NND-F	20k Ω thermistor	TE-END-F	20k Ω thermistor

## SPECIFICATIONS

Accuracy: Thermistor temp sensor:  $\pm 0.22^{\circ}$ C @ 25°C ( $\pm 0.4^{\circ}$ F @ 77°F); RTD temp sensor: DIN class B;  $\pm 0.3^{\circ}$ C @ 0°C ( $\pm 54^{\circ}$ F @  $32^{\circ}$ F). Temperature Limits: -40 to 140°F (-40 to 60°C). Housing Material: ABS plastic. Weight: 0.3 lb (136 g).